

Practical: 1

Aim: To study and implement input and output operations in the C programming language using standard library functions.

```
#include <stdio.h>

int main() {
    int num;
    float marks;
    char grade;

    // Input operations
    printf("Enter an integer: ");
    scanf("%d", &num);


    printf("Enter a float value: ");
    scanf("%f", &marks);

    printf("Enter a character: ");
    scanf(" %c", &grade);

    // Output operations
    printf("\nEnter Integer = %d", num);
    printf("\nEnter Float = %.2f", marks);
    printf("\nEnter Character = %c", grade);

    return 0;
}
```

Output :

A screenshot of a terminal window with a dark background and light-colored text. It shows the output of the C program. The first three lines are prompts for user input: 'Enter an integer: 45', 'Enter a float value: 88.567', and 'Enter a character: A'. The next three lines are the program's output: 'Entered Integer = 45', 'Entered Float = 88.57', and 'Entered Character = A'.

```
Enter an integer: 45
Enter a float value: 88.567
Enter a character: A

Entered Integer = 45
Entered Float = 88.57
Entered Character = A
```

Practical: 2

Aim: To write a C program to generate the Fibonacci series up to n terms.

```
#include <stdio.h>

int main()
{
    int n, i;
    int a = 0, b = 1, c;

    printf("Enter the number of terms: ");
    scanf("%d", &n);


    printf("Fibonacci Series: ");

    for(i = 1; i <= n; i++)
    {
        printf("%d ", a);

        c = a + b;
        a = b;
        b = c;
    }

    return 0;
}
```

Output :

A screenshot of a terminal window with a dark background. It shows the output of the C program. The first line is "Enter the number of terms: 5" and the second line is "Fibonacci Series: 0 1 1 2 3".

```
Enter the number of terms: 5
Fibonacci Series: 0 1 1 2 3
```

Practical: 3

Aim: To study and demonstrate different operators and expressions used in the C programming language.

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int a, b;
```

```
    printf("Enter two integers: ");
```

```
    scanf("%d %d", &a, &b);
```

```
    // Arithmetic
```

```
    printf("\n--- Arithmetic Operators ---");
```

```
    printf("\nAddition: %d", a + b);
```

```
    printf("\nSubtraction: %d", a - b);
```

```
    printf("\nMultiplication: %d", a * b);
```

```
    printf("\nDivision: %d", a / b);
```

```
    printf("\nModulus: %d", a % b);
```

```
    // Relational
```

```
    printf("\n\n--- Relational Operators ---");
```

```
    printf("\nEqual: %d", a == b);
```

```
    printf("\nNot Equal: %d", a != b);
```

```
    printf("\nGreater: %d", a > b);
```

```
    printf("\nLess: %d", a < b);
```

```
    // Logical
```

```
    printf("\n\n--- Logical Operators ---");
```

```
    printf("\nAND (a>b && a!=b): %d", (a > b && a != b));
```

```
    printf("\nOR (a>b || a<b): %d", (a > b || a < b));
```

```
    printf("\nNOT (!a): %d", !a);
```

```
    // Assignment
```

```
    printf("\n\n--- Assignment Operators ---");
```

```
    int c = a;
```

```
    c += b;
```

```
    printf("\nAfter c += b: %d", c);
```

```
    // Increment / Decrement
```

```
    printf("\n\n--- Increment / Decrement ---");
```

```
    printf("\nPre-increment a: %d", ++a);
```

```
    printf("\nPre-decrement b: %d", --b);
```

```
    return 0;
```

```
}
```

Output :

Arithmetic Operators:

```
a + b = 15  
a - b = 5  
a * b = 50  
a / b = 2  
a % b = 0
```

Relational Operators:

```
a > b = 1  
a < b = 0  
a == b = 0
```

Logical Operators:

```
(a > 0 && b > 0) = 1  
(a < 0 || b > 0) = 1  
!(a > b) = 0
```

Assignment Operator (c += b): 15

Increment and Decrement Operators:

```
++a = 11  
--b = 4
```

Practical: 4

Aim: To study and demonstrate the use of conditional statements and branching in the C programming language.

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int num, marks, choice;
```

```
    printf("Enter a number: ");
```

```
    scanf("%d", &num);
```

```
    printf("Enter marks (0-100): ");
```

```
    scanf("%d", &marks);
```

```
    printf("\n--- IF Statement ---");
```

```
    if(num > 0)
```

```
    {
```

```
        printf("\nNumber is Positive");
```

```
    }
```

```
    printf("\n\n--- IF-ELSE ---");
```

```
    if(num % 2 == 0)
```

```
        printf("\nEven Number");
```

```
    else
```

```
        printf("\nOdd Number");
```

```
    printf("\n\n--- ELSE-IF LADDER ---");
```

```
    if(marks >= 90)
```

```
        printf("\nGrade: A+");
```

```
    else if(marks >= 75)
```

```
        printf("\nGrade: A");
```

```
    else if(marks >= 60)
```

```
        printf("\nGrade: B");
```

```
    else if(marks >= 40)
```

```
        printf("\nGrade: C");
```

```
    else
```

```
        printf("\nFail");
```

```
    printf("\n\n--- NESTED IF ---");
```

```
    if(num > 0)
```

```
    {
```

```
        if(num < 100)
```


```
            printf("\nNumber is Positive and less than 100");
```

```
        else
```


```
            printf("\nNumber is Positive but greater than 100");
```

```
}  
else  
{  
    printf("\nNumber is Negative or Zero");  
  
}  
  
printf("\n\n--- SWITCH CASE ---");  
printf("\nEnter choice (1-3): ");  
scanf("%d", &choice);  
  
switch(choice)  
{  
    case 1:  
        printf("\nYou selected Addition");  
        break;  
  
    case 2:  
        printf("\nYou selected Subtraction");  
        break;  
  
    case 3:  
        printf("\nYou selected Multiplication");  
        break;  
  
    default:  
        printf("\nInvalid Choice");  
}  
  
return 0;  
}
```


Output :



```
Enter marks: 95  
Grade A
```



```
Enter marks: 50  
Grade C
```



```
Enter marks: 42  
Fail
```

Practical: 5

Aim: To study and implement different looping statements in the C Programming Language using a C program.

```
#include <stdio.h>

int main() {
    int i, n, sum = 0;

    // FOR LOOP
    printf("FOR LOOP:\n");
    for(i = 1; i <= 5; i++) {
        printf("%d ", i);
    }

    // WHILE LOOP
    printf("\n\nWHILE LOOP:\n");
    i = 1;
    while(i <= 5) {
        printf("%d ", i);
        i++;
    }

    // DO-WHILE LOOP
    printf("\n\nDO-WHILE LOOP:\n");
    i = 1;
    do {
        printf("%d ", i);
        i++;
    } while(i <= 5);

    // SUM OF N NUMBERS
    printf("\n\nEnter a number: ");
    scanf("%d", &n);

    for(i = 1; i <= n; i++) {
        sum = sum + i;
    }

    printf("Sum of first %d natural numbers = %d\n", n, sum);

    return 0;
}
```

Output :

```
FOR LOOP:  
1 2 3 4 5  
  
WHILE LOOP:  
1 2 3 4 5  
  
DO-WHILE LOOP:  
1 2 3 4 5  
  
Enter a number: 5  
Sum of first 5 natural numbers = 15
```


Practical: 6

Aim: To study and demonstrate the working of one-dimensional arrays in the C programming language.

```
#include <stdio.h>


int main() {
    int arr[5], i;

    // Input elements
    printf("Enter 5 elements:\n");
    for(i = 0; i < 5; i++) {
        scanf("%d", &arr[i]);
    }

    // Display elements
    printf("The array elements are:\n");
    for(i = 0; i < 5; i++) {
        printf("%d ", arr[i]);
    }

    return 0;
}
```

Output :



The screenshot shows the execution of the C program. It prompts the user to 'Enter 5 elements:' and then displays the entered values: 10, 20, 30, 40, and 50. Below this, it prompts 'The array elements are:' and displays the same values: 10 20 30 40 50.

Practical: 7

Aim: To study and demonstrate the working of two-dimensional arrays in C programming by performing basic operations such as input, storage, and display of matrix elements.

```
#include <stdio.h>

int main() {
    int rows, cols;

    printf("Enter number of rows and columns: ");
    scanf("%d %d", &rows, &cols);

    int matrix[rows][cols];

    printf("Enter elements of matrix:\n");


    // Input matrix elements
    for(int i = 0; i < rows; i++) {
        for(int j = 0; j < cols; j++) {
            scanf("%d", &matrix[i][j]);
        }
    }

    // Display matrix
    printf("The matrix is:\n");

    for(int i = 0; i < rows; i++) {
        for(int j = 0; j < cols; j++) {
            printf("%d ", matrix[i][j]);
        }
        printf("\n");
    }

    return 0;
}
```

Output :



```
Enter number of rows and columns: 2 3
Enter elements of matrix:
1 2 3
4 5 6

Matrix is:
1 2 3
4 5 6
```

Practical: 8

Aim: To study and demonstrate the working of strings in C programming using basic string operations such as input, output, length calculation, and copying.

```
#include <stdio.h>
#include <string.h>

int main() {
    char str1[100], str2[100];

    // Input string
    printf("Enter first string: ");
    fgets(str1, sizeof(str1), stdin);

    // Removing newline character
    str1[strcspn(str1, "\n")] = '\0';

    // Copying string
    strcpy(str2, str1);

    // Displaying strings
    printf("\nOriginal String: %s\n", str1);
    printf("Copied String: %s\n", str2);

    // Length of string
    printf("Length of string: %lu\n", strlen(str1));

    return 0;
}
```

Output :

```
Enter first string: Hello World

Original String: Hello World
Copied String: Hello World
Length of string: 11
```

Practical: 9

Aim: To study and implement user-defined functions in C programming and understand how they improve modularity and code reusability.

```
#include <stdio.h>

// Function to calculate sum
int add(int a, int b) {
    return a + b;
}

// Function to calculate multiplication
int multiply(int a, int b) {
    return a * b;
}

int main() {
    int num1, num2;
    int sum, product;


    printf("Enter two numbers: ");
    scanf("%d %d", &num1, &num2);

    // Calling user-defined functions
    sum = add(num1, num2);
    product = multiply(num1, num2);

    printf("Sum = %d\n", sum);
    printf("Product = %d\n", product);

    return 0;
}
```

Output :

A screenshot of a terminal window showing the output of the C program. The text is as follows:

```
Enter two numbers: 6 4
Sum = 10
Product = 24
```

Practical: 10

Aim: To demonstrate Call by Value and Return by Value in C programming.

```
#include <stdio.h>

void show(int x) {
    x = x + 10;
    printf("Inside function: %d\n", x);
}


int main() {
    int a = 5;

    show(a);

    printf("Hello\n");

    return 0;
}
```

Output :

A screenshot of a terminal window with a dark background. It displays the output of the C program: 'Inside function: 15' on the first line, 'Outside function: 5' on the second line, and 'Hello' on the third line.

```
Inside function: 15
Outside function: 5
Hello
```